



### Bearing No. 6330

D	320 mm
d	150 mm
B	65 mm
C	65 mm
f0	13.9
Cu	16.6
Cr	343
C0r	284
Bore	5.906 Inch   150 Millimeter
Noun	Bearing
UNSPSC	31171504
Weight	26,2 Kg
r(min)	4
r min.	4 mm
da min.	166 mm
ra(max)	3
Da max.	304 mm
Da(max)	304
da(min)	166
ra max.	3 mm
Category	Single Row Ball Bearing
Oil lub.	2300
Inventory	0.0
Enclosure	Open
Size (mm)	150x320x65
Snap Ring	No
Width (mm)	65
Grease lub.	1900
Bearing No.	6330

Weight / LBS	57.76104
Product Group	B00308
Cage Material	Steel
Inch - Metric	Metric
Keyword String	Ball
Bearing number	6330
Other Features	Deep Groove
Rolling Element	Ball Bearing
Precision Class	ABEC 1   ISO P0
(Refer.)Mass(kg)	26.2
Manufacturer URL	<a href="http://www.koyousa.com">http://www.koyousa.com</a>
Inner Race Width	0 Inch   0 Millimeter
Long Description	150MM Bore; 320MM Outside Diameter; 65MM Outer Race Width; Open; Ball Bearing; ABEC 1   ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Cage
Outer Race Width	2.559 Inch   65 Millimeter
Outside Diameter	12.598 Inch   320 Millimeter
Manufacturer Name	KOYO
Weight / Kilogram	0
Internal Clearance	C0-Medium
Bore Diameter (mm)	150
Outer Diameter (mm)	320
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.68
(Oil) Lubrication Speed	2300 r/min
Internal Special Features	No

(Grease) Lubrication Speed	1900 r/min
Basic static load rating (C0)	284 kN
Basic dynamic load rating (C)	275 kN
Maximum Capacity / Filling Slot	No