



**Bearing No. 63304LLU**

C	22,200 mm
d	20,000 mm
B	22,200 mm
D	52,000 mm
Bore	0.787 Inch   20 Millimeter
Noun	Bearing
UNSPSC	31171504
series:	633
Category	Single Row Ball Bearing
Size (mm)	20x52x22.200
Inventory	0.0
Enclosure	2 Seals
Snap Ring	No
Width (mm)	22,200
bore type:	Round
Weight / LBS	0.48
Cage Material	Steel
Inch - Metric	Metric
Product Group	B00308
closure type:	Double Sealed
bore diameter:	20 mm
overall width:	22.2 mm
Keyword String	Ball
fillet radius:	1.1 mm
cage material:	Steel
Bearing number	63304LLU
Other Features	Deep Groove   Cartridge Type   Double Lip Friction Nitrile Rubber Seal   -20 To 120 Deg C   Shell Alvania

	Prelubricated
Enclosure Type	Contact Seal
finish/coating:	Uncoated
Rolling Element	Ball Bearing
Precision Class	ABEC 1   ISO P0
Manufacturer URL	<a href="http://www.ntnamerica.com">http://www.ntnamerica.com</a>
Outside Diameter	2.047 Inch   52 Millimeter
Outer Race Width	0.875 Inch   22.225 Millimeter
Inner Race Width	0 Inch   0 Millimeter
Long Description	20MM Bore; 52MM Outside Diameter; 22.225MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1   ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Ca
outer ring width:	22.20 mm
inner ring width:	22.20 mm
Manufacturer Name	NTN
Weight / Kilogram	0
bearing material:	High Carbon Chrome Steel
outside diameter:	52 mm
precision rating:	ISO Class 0
Bore Diameter (mm)	20,000
Internal Clearance	C0-Medium
Outer Diameter (mm)	52,000
internal clearance:	CN
snap ring included:	Without Snap Ring
Minimum Buy Quantity	N/A

row type & fill slot:	Single Row Non-Fill Slot
maximum rpm (grease):	10000 rpm
static load capacity:	7900 N
Harmonized Tariff Code	8482.10.50.68
dynamic load capacity:	15900 N
Internal Special Features	No
manufacturer product page:	<a href="#">Click here</a>
operating temperature range:	-40 to 120 °C
Maximum Capacity / Filling Slot	No