



Bearing No. 63305LLU

C	25,400 mm
d	25,000 mm
B	25,400 mm
D	62,000 mm
Bore	0.984 Inch 25 Millimeter
Noun	Bearing
UNSPSC	31171504
series:	633
Category	Single Row Ball Bearing
Size (mm)	25x62x25.400
Inventory	0.0
Enclosure	2 Seals
Snap Ring	No
Width (mm)	25,400
bore type:	Round
Weight / LBS	0.78
Cage Material	Steel
Inch - Metric	Metric
Product Group	B00308
closure type:	Double Sealed
bore diameter:	25 mm
overall width:	25.4 mm
Keyword String	Ball
fillet radius:	1.1 mm
cage material:	Steel
Bearing number	63305LLU
Other Features	Deep Groove Cartridge Type Double Lip Friction Nitrile Rubber Seal -20 To 120 Deg C Shell Alvania

	Prelubricated
Enclosure Type	Contact Seal
finish/coating:	Uncoated
Rolling Element	Ball Bearing
Precision Class	ABEC 1 ISO P0
Manufacturer URL	http://www.ntnamerica.com
Outside Diameter	2.441 Inch 62 Millimeter
Outer Race Width	1 Inch 25.4 Millimeter
Inner Race Width	0 Inch 0 Millimeter
Long Description	25MM Bore; 62MM Outside Diameter; 25.4MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Cage
outer ring width:	25.40 mm
inner ring width:	25.40 mm
Manufacturer Name	NTN
Weight / US pound	0.741
bearing material:	High Carbon Chrome Steel
outside diameter:	62 mm
precision rating:	ISO Class 0
Bore Diameter (mm)	25,000
Internal Clearance	C0-Medium
Outer Diameter (mm)	62,000
internal clearance:	CN
snap ring included:	Without Snap Ring
Minimum Buy Quantity	N/A
row type & fill slot:	Single Row Non-Fill Slot

maximum rpm (grease):	8100 rpm
static load capacity:	10900 N
Harmonized Tariff Code	8482.10.50.68
dynamic load capacity:	21200 N
Internal Special Features	No
manufacturer product page:	Click here
operating temperature range:	-40 to 120 °C
Maximum Capacity / Filling Slot	No