



Bearing No. 63308LLU

C	36,500 mm
d	40,000 mm
B	36,500 mm
D	90,000 mm
Bore	1.575 Inch 40 Millimeter
Noun	Bearing
UNSPSC	31171504
series:	633
Category	Single Row Ball Bearing
Size (mm)	40x90x36.500
Inventory	0.0
Enclosure	2 Seals
Snap Ring	No
Width (mm)	36,500
bore type:	Round
Weight / LBS	2.06
Cage Material	Steel
Inch - Metric	Metric
Product Group	B00308
closure type:	Double Sealed
bore diameter:	40 mm
overall width:	36.5 mm
Keyword String	Ball
fillet radius:	1.5 mm
cage material:	Steel
Bearing number	63308LLU
Other Features	Deep Groove Cartridge Type Double Lip Friction Nitrile Rubber Seal -20 To 120 Deg C Shell Alvania

	Prelubricated
Enclosure Type	Contact Seal
finish/coating:	Uncoated
Rolling Element	Ball Bearing
Precision Class	ABEC 1 ISO P0
Manufacturer URL	http://www.ntnamerica.com
Outside Diameter	3.543 Inch 90 Millimeter
Outer Race Width	1.438 Inch 36.53 Millimeter
Inner Race Width	0 Inch 0 Millimeter
Long Description	40MM Bore; 90MM Outside Diameter; 36.53MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Cag
outer ring width:	36.50 mm
inner ring width:	36.50 mm
Manufacturer Name	NTN
Weight / Kilogram	0
bearing material:	High Carbon Chrome Steel
outside diameter:	90 mm
precision rating:	ISO Class 0
Bore Diameter (mm)	40,000
Internal Clearance	C0-Medium
Outer Diameter (mm)	90,000
internal clearance:	CN
snap ring included:	Without Snap Ring
Minimum Buy Quantity	N/A

row type & fill slot:	Single Row Non-Fill Slot
maximum rpm (grease):	5300 rpm
static load capacity:	24000 N
Harmonized Tariff Code	8482.10.50.68
dynamic load capacity:	40500 N
Internal Special Features	No
manufacturer product page:	Click here
operating temperature range:	-40 to 120 °C
Maximum Capacity / Filling Slot	No