



Bearing No. 6826VV

r	1.1
d	130 mm
D	165 mm
B	18 mm
C	18 mm
D_	165
B_	18
ra	1
C0	44
fo	17.1
Z_	24
DI_	137.181
SRE	5.34
D_a	158.5
DE_	157.819
DA_	10.319
SRI	5.34
SREN	-0.025
SBRG	18
SREX	0.025
KBRG	6151
Bore	5.118 Inch 130 Millimeter
mass	0.758
Noun	Bearing
SRIX	0.025
SRIN	-0.025
SDM_	147.5
bomp	0
yobi	6826VV

Weight	0,758 Kg
da min	136.5
LangID	1
da max	138 mm
C_conv	37000
ALPHA_	0
UNSPSC	31171504
r min.	1,1 mm
hidYobi	6826VV
ra max.	1 mm
GRS rpm	3600
Da max.	158,5 mm
da min.	136,5 mm
hidTable	ecat_NSRDGB
Category	Single Row Ball Bearing
Snap Ring	No
Size (mm)	130x165x18
Enclosure	2 Seals
Inventory	0.0
Width (mm)	18
bore type:	Round
Prod_Type3	DGBB_SR_VV
Weight / LBS	0.83
Product Group	B00308
Cage Material	Steel
closure type:	Double Sealed
Inch - Metric	Metric
Bearing number	6826VV
Keyword String	Ball
overall width:	18 mm
Enclosure Type	Non-Contact Seal
bore diameter:	130 mm

Precision Class	ABEC 1 ISO P0
Rolling Element	Ball Bearing
Outer Race Width	0.709 Inch 18 Millimeter
Long Description	130MM Bore; 165MM Outside Diameter; 18MM Outer Race Diameter; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Outside Diameter	6.496 Inch 165 Millimeter
Manufacturer URL	http://www.nskamericas.com
Manufacturer Name	NSK
Weight / Kilogram	0.82
outside diameter:	165 mm
Bore Diameter (mm)	130
Internal Clearance	C0-Medium
Outer Diameter (mm)	165
internal clearance:	Normal Clearance
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.68
Manufacturer Item Number	6826VV
manufacturer upc number:	029176030369
Internal Special Features	No
(Grease) Lubrication Speed	3 600 r/min
Basic static load rating (C0)	44 kN
Basic dynamic load rating (C)	37 kN

Maximum Capacity / Filling Slot	No
------------------------------------	----