



Bearing No. 6826ZZS

|        |         |
|--------|---------|
| r      | 1.1     |
| d      | 130 mm  |
| D      | 165 mm  |
| B      | 18 mm   |
| C      | 18 mm   |
| fo     | 17.1    |
| ra     | 1       |
| D_     | 165     |
| C0     | 44      |
| B_     | 18      |
| Z_     | 24      |
| SRI    | 5.34    |
| DE_    | 157.819 |
| DA_    | 10.319  |
| DI_    | 137.181 |
| SRE    | 5.34    |
| D_a    | 158.5   |
| SREX   | 0.025   |
| mass   | 0.758   |
| SRIN   | -0.025  |
| bomp   | 0       |
| SREN   | -0.025  |
| yobi   | 6826ZZS |
| SDM_   | 147.5   |
| KBRG   | 6141    |
| SBRG   | 18      |
| SRIX   | 0.025   |
| C_conv | 37000   |
| ALPHA_ | 0       |
| da min | 136.5   |
|        |         |

|                               |             |
|-------------------------------|-------------|
| Weight                        | 0,758 Kg    |
| r min.                        | 1,1 mm      |
| LangID                        | 1           |
| da max                        | 138 mm      |
| ra max.                       | 1 mm        |
| da min.                       | 136,5 mm    |
| Da max.                       | 158,5 mm    |
| GRS rpm                       | 3600        |
| hidYobi                       | 6826ZZS     |
| hidTable                      | ecat_NSRDGB |
| Size (mm)                     | 130x165x18  |
| Prod_Type3                    | DGBB_SR_ZZ  |
| Width (mm)                    | 18          |
| Bearing number                | 6826ZZS     |
| Bore Diameter (mm)            | 130         |
| Outer Diameter (mm)           | 165         |
| (Grease) Lubrication Speed    | 3 600 r/min |
| Basic dynamic load rating (C) | 37 kN       |
| Basic static load rating (C0) | 44 kN       |