



Bearing No. 63310ZZ

D	110,000 mm
d	50,000 mm
B	44,400 mm
C	44,400 mm
Noun	Bearing
Bore	1.969 Inch 50 Millimeter
UNSPSC	31171504
series:	633
Category	Single Row Ball Bearing
Snap Ring	No
Enclosure	2 Metal Shields
Size (mm)	50x110x44.400
Inventory	0.0
bore type:	Round
Width (mm)	44,400
Weight / LBS	3.75
closure type:	Double Shielded
Product Group	B00308
Cage Material	Steel
Inch - Metric	Metric
overall width:	44.4 mm
bore diameter:	50 mm
fillet radius:	2 mm
Keyword String	Ball
cage material:	Steel
Bearing number	63310ZZ
Other Features	Deep Groove Cartridge Type Shell Alvania Prelubricated
finish/coating:	Uncoated

Rolling Element	Ball Bearing
Precision Class	ABEC 1 ISO P0
Long Description	50MM Bore; 110MM Outside Diameter; 44.45MM Outer Race Width; 2 Metal Shields; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance;
Manufacturer URL	http://www.ntnamerica.com
Outer Race Width	1.75 Inch 44.45 Millimeter
Outside Diameter	4.331 Inch 110 Millimeter
Inner Race Width	0 Inch 0 Millimeter
outer ring width:	44.40 mm
inner ring width:	44.40 mm
Manufacturer Name	NTN
Weight / Kilogram	0
bearing material:	High Carbon Chrome Steel
outside diameter:	110 mm
precision rating:	ISO Class 0
Internal Clearance	C0-Medium
Bore Diameter (mm)	50,000
Outer Diameter (mm)	110,000
internal clearance:	CN
snap ring included:	Without Snap Ring
Minimum Buy Quantity	N/A
row type & fill slot:	Single Row Non-Fill Slot
maximum rpm (grease):	6400 rpm
static load capacity:	38500 N

Harmonized Tariff Code	8482.10.50.68
dynamic load capacity:	62000 N
Internal Special Features	No
manufacturer product page:	Click here
operating temperature range:	-40 to 120 °C
Maximum Capacity / Filling Slot	No