



**Bearing No. 63312ZZ**

D	130,000 mm
d	60,000 mm
B	53,975 mm
C	53,975 mm
Noun	Bearing
Bore	2.362 Inch   60 Millimeter
UNSPSC	31171504
Category	Single Row Ball Bearing
Size (mm)	60x130x53.975
Snap Ring	No
Inventory	0.0
Enclosure	2 Metal Shields
bore type:	Round
Width (mm)	53,975
Weight / LBS	6.5
Product Group	B00308
closure type:	Double Shielded
Cage Material	Steel
Inch - Metric	Metric
overall width:	54 mm
bore diameter:	60 mm
cage material:	Steel
Keyword String	Ball
fillet radius:	2.1 mm
Bearing number	63312ZZ
Other Features	Deep Groove   Cartridge Type   Shell Alvania Prelubricated
Rolling Element	Ball Bearing
Precision Class	ABEC 1   ISO P0

finish/coating:	Uncoated
Long Description	60MM Bore; 130MM Outside Diameter; 53.98MM Outer Race Width; 2 Metal Shields; Ball Bearing; ABEC 1   ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance;
Manufacturer URL	<a href="http://www.ntnamerica.com">http://www.ntnamerica.com</a>
Outer Race Width	2.125 Inch   53.98 Millimeter
Outside Diameter	5.118 Inch   130 Millimeter
Inner Race Width	0 Inch   0 Millimeter
outer ring width:	54 mm
inner ring width:	54 mm
Manufacturer Name	NTN
bearing material:	High Carbon Chrome Steel
Weight / Kilogram	0
precision rating:	ISO Class 0
outside diameter:	130 mm
Bore Diameter (mm)	60,000
Internal Clearance	C0-Medium
Outer Diameter (mm)	130,000
snap ring included:	Without Snap Ring
internal clearance:	CN
Minimum Buy Quantity	N/A
row type & fill slot:	Single Row Non-Fill Slot
maximum rpm (grease):	5400 rpm
static load capacity:	52000 N
Harmonized Tariff Code	8482.10.50.68

dynamic load capacity:	82000 N
Internal Special Features	No
manufacturer product page:	<a href="#">Click here</a>
operating temperature range:	-40 to 120 °C
Maximum Capacity / Filling Slot	No