



**Bearing No. 63313LLB**

C	58,700 mm
d	65,000 mm
B	58,700 mm
D	140,000 mm
Bore	2.559 Inch   65 Millimeter
Noun	Bearing
UNSPSC	31171504
series:	633
Category	Single Row Ball Bearing
Size (mm)	65x140x58.700
Inventory	0.0
Enclosure	2 Seals
Snap Ring	No
Width (mm)	58,700
bore type:	Round
Weight / LBS	8.17
Cage Material	Steel
Inch - Metric	Metric
Product Group	B00308
closure type:	Double Sealed
bore diameter:	65 mm
overall width:	58.7 mm
Keyword String	Ball
fillet radius:	2.1 mm
cage material:	Steel
Bearing number	63313LLB
Other Features	Deep Groove   Cartridge Type   Non-Friction Nitrile Rubber Seal   Shell Alvania Prelubricated

Enclosure Type	Non-Contact Seal
finish/coating:	Uncoated
Rolling Element	Ball Bearing
Precision Class	ABEC 1   ISO P0
Manufacturer URL	<a href="http://www.ntnamerica.com">http://www.ntnamerica.com</a>
Outside Diameter	5.512 Inch   140 Millimeter
Outer Race Width	2.312 Inch   58.72 Millimeter
Inner Race Width	0 Inch   0 Millimeter
Long Description	65MM Bore; 140MM Outside Diameter; 58.72MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1   ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Ca
outer ring width:	58.70 mm
inner ring width:	58.70 mm
Manufacturer Name	NTN
Weight / Kilogram	0
bearing material:	High Carbon Chrome Steel
outside diameter:	140 mm
precision rating:	ISO Class 0
Bore Diameter (mm)	65,000
Internal Clearance	C0-Medium
Outer Diameter (mm)	140,000
internal clearance:	CN
snap ring included:	Without Snap Ring
Minimum Buy Quantity	N/A
row type & fill slot:	Single Row Non-Fill Slot

maximum rpm (grease):	4900 rpm
static load capacity:	60000 N
Harmonized Tariff Code	8482.10.50.68
dynamic load capacity:	92500 N
Internal Special Features	No
manufacturer product page:	<a href="#">Click here</a>
operating temperature range:	-40 to 120 °C
Maximum Capacity / Filling Slot	No