



**Bearing No. 63314LLB**

C	63,500 mm
d	70,000 mm
B	63,500 mm
D	150,000 mm
Bore	2.756 Inch   70 Millimeter
Noun	Bearing
UNSPSC	31171504
series:	633
Category	Single Row Ball Bearing
Size (mm)	70x150x63.500
Inventory	0.0
Enclosure	2 Seals
Snap Ring	No
Width (mm)	63,500
bore type:	Round
Weight / LBS	10.5
Cage Material	Steel
Inch - Metric	Metric
Product Group	B00308
closure type:	Double Sealed
bore diameter:	70 mm
overall width:	63.5 mm
Keyword String	Ball
fillet radius:	2.1 mm
cage material:	Steel
Bearing number	63314LLB
Other Features	Deep Groove   Cartridge Type   Non-Friction Nitrile Rubber Seal   Shell Alvania Prelubricated

Enclosure Type	Non-Contact Seal
finish/coating:	Uncoated
Rolling Element	Ball Bearing
Precision Class	ABEC 1   ISO P0
Manufacturer URL	<a href="http://www.ntnamerica.com">http://www.ntnamerica.com</a>
Outer Race Width	2.5 Inch   63.5 Millimeter
Inner Race Width	0 Inch   0 Millimeter
Outside Diameter	5.906 Inch   150 Millimeter
Long Description	70MM Bore; 150MM Outside Diameter; 63.5MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1   ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Cag
outer ring width:	63.50 mm
inner ring width:	63.50 mm
Manufacturer Name	NTN
Weight / Kilogram	0
bearing material:	High Carbon Chrome Steel
outside diameter:	150 mm
precision rating:	ISO Class 0
Bore Diameter (mm)	70,000
Internal Clearance	C0-Medium
Outer Diameter (mm)	150,000
internal clearance:	CN
snap ring included:	Without Snap Ring
Minimum Buy Quantity	N/A
row type & fill slot:	Single Row Non-Fill Slot
maximum rpm (grease):	4600 rpm

static load capacity:	68000 N
Harmonized Tariff Code	8482.10.50.68
dynamic load capacity:	104000 N
Internal Special Features	No
manufacturer product page:	<a href="#">Click here</a>
operating temperature range:	-40 to 120 °C
Maximum Capacity / Filling Slot	No