



Bearing No. 63316LLU

C	68,300 mm
d	80,000 mm
B	68,300 mm
D	170,000 mm
Bore	3.15 Inch 80 Millimeter
Noun	Bearing
UNSPSC	31171504
series:	633
Category	Single Row Ball Bearing
Size (mm)	80x170x68.300
Inventory	0.0
Enclosure	2 Seals
Snap Ring	No
Width (mm)	68,300
bore type:	Round
Weight / LBS	13.603
Cage Material	Steel
Inch - Metric	Metric
Product Group	B00234
closure type:	Double Sealed
bore diameter:	80 mm
overall width:	68.3 mm
Keyword String	Ball
fillet radius:	2.1 mm
cage material:	Steel
Bearing number	63316LLU
Other Features	Deep Groove Cartridge Type Double Lip Friction Nitrile Rubber Seal -20 To 120 Deg C
Enclosure Type	Contact Seal

finish/coating:	Uncoated
Rolling Element	Ball Bearing
Precision Class	ABEC 1 ISO P0
Manufacturer URL	http://www.ntnamerica.com
Long Description	80MM Bore; 170MM Outside Diameter; 68.28MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Ca
Outer Race Width	2.688 Inch 68.28 Millimeter
Outside Diameter	6.693 Inch 170 Millimeter
Inner Race Width	0 Inch 0 Millimeter
Manufacturer Name	NTN
Weight / Kilogram	0
bearing material:	High Carbon Chrome Steel
precision rating:	ISO Class 0
outside diameter:	170 mm
outer ring width:	68.30 mm
inner ring width:	68.30 mm
Internal Clearance	C0-Medium
Bore Diameter (mm)	80,000
internal clearance:	CN
Outer Diameter (mm)	170,000
snap ring included:	Without Snap Ring
Minimum Buy Quantity	N/A
row type & fill slot:	Single Row Non-Fill Slot
maximum rpm (grease):	2700 rpm

static load capacity:	86500 N
Harmonized Tariff Code	8482.10.50.68
dynamic load capacity:	123000 N
Manufacturer Item Number	63316LLU
Internal Special Features	No
manufacturer product page:	Click here
operating temperature range:	-40 to 120 °C
Maximum Capacity / Filling Slot	No