



Bearing No. 6824NR

f	1,7 mm
r	1
d	120 mm
D	150 mm
B	16 mm
C	16 mm
a	2,5 mm
b	1,9 mm
D2	155,7 mm
B_	16
Cy	3.9
ra	1
C0	35.5
fo	17.3
D_	150
D1	147,6 mm
rn	0,5 mm
Z_	27
Dx	157
ro	0.6
DE_	143.731
DA_	8.731
SRI	4.52
D_a	145
SRE	4.52
DI_	126.269
SRIN	-0.02
yobi	6824NR
SBRG	18
bomp	0

SREX	0.02
KBRG	6101
SREN	-0.02
SDM_	135
SRIX	0.02
mass	0.537
C_conv	28900
r min.	1 mm
da max	127 mm
ALPHA_	0
Weight	0,537 Kg
da min	125
LangID	1
GRS rpm	4000
Da max.	145 mm
hidYobi	6824NR
Oil rpm	4800
da min.	125 mm
r0 max.	0,6 mm
ra max.	1 mm
hidTable	ecat_NSRDGB
Size (mm)	120x150x16
Prod_Type3	DGBB_SR_NR_OT
Width (mm)	16
Bearing number	6824NR
Bore Diameter (mm)	120
Outer Diameter (mm)	150
(Oil) Lubrication Speed	4 800 r/min
(Grease) Lubrication Speed	4 000 r/min
Basic dynamic load rating (C)	28,9 kN
Basic static load rating	35,5 kN

(C0)	
------	--