



Bearing No. 6822LLB

D	140,000 mm
d	110,000 mm
B	16,000 mm
C	16,000 mm
Bore	4.331 Inch 110 Millimeter
Noun	Bearing
UNSPSC	31171504
Category	Single Row Ball Bearing
Size (mm)	110x140x16
Inventory	0.0
Snap Ring	No
Enclosure	2 Seals
bore type:	Round
Width (mm)	16,000
Weight / LBS	1.094
Cage Material	Steel
Inch - Metric	Metric
Product Group	B00308
closure type:	Double Sealed
Other Features	Deep Groove Non-Friction Nitrile Rubber Seal Shell Alvania Prelubricated
bore diameter:	110 mm
overall width:	16 mm
cage material:	Steel
fillet radius:	1 mm
Bearing number	6822LLB
Keyword String	Ball
Enclosure Type	Non-Contact Seal

Rolling Element	Ball Bearing
Precision Class	ABEC 1 ISO P0
finish/coating:	Uncoated
Long Description	110MM Bore; 140MM Outside Diameter; 16MM Outer Race Diameter; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Manufacturer URL	http://www.ntnamerica.com
Outer Race Width	0.63 Inch 16 Millimeter
Outside Diameter	5.512 Inch 140 Millimeter
Inner Race Width	0 Inch 0 Millimeter
precision rating:	ISO Class 0
outer ring width:	16 mm
inner ring width:	16 mm
Manufacturer Name	NTN
bearing material:	High Carbon Chrome Steel
Weight / Kilogram	0.495
outside diameter:	140 mm
Bore Diameter (mm)	110,000
Internal Clearance	C0-Medium
Outer Diameter (mm)	140,000
snap ring included:	Without Snap Ring
internal clearance:	CN
Minimum Buy Quantity	N/A
maximum rpm (grease):	4300 rpm
static load capacity:	28200 N
row type & fill slot:	Single Row Non-Fill Slot
dynamic load capacity:	24900 N

Harmonized Tariff Code	8482.10.50.68
Manufacturer Item Number	6822LLB/5C
Internal Special Features	No
manufacturer product page:	Click here
operating temperature range:	-40 to 120 °C
Maximum Capacity / Filling Slot	No