



Bearing No. 6822N

a	2,5 mm
r	1
d	110 mm
D	140 mm
B	16 mm
C	16 mm
b	1,9 mm
fo	17.1
B_	16
ra	1
C0	32.5
D1	137,6 mm
D_	140
Z_	25
rn	0,5 mm
ro	0.6
DE_	133.731
SRI	4.52
D_a	135
DA_	8.731
SRE	4.52
DI_	116.269
yobi	6822N
mass	0.497
SBRG	18
bomp	0
KBRG	6101
SREX	0.02
SREN	0
SRIN	-0.02

SDM_	125
SRIX	0.02
ALPHA_	0
r min.	1 mm
C_conv	28100
da max	117 mm
da min	115
Weight	0,497 Kg
LangID	1
ra max.	1 mm
Da max.	135 mm
Oil rpm	5300
da min.	115 mm
r0 max.	0,6 mm
hidYobi	6822N
GRS rpm	4300
hidTable	ecat_NSRDGB
Size (mm)	110x140x16
Prod_Type3	DGBB_SR_N_OT
Width (mm)	16
Bearing number	6822N
Bore Diameter (mm)	110
Outer Diameter (mm)	140
(Oil) Lubrication Speed	5 300 r/min
(Grease) Lubrication Speed	4 300 r/min
Basic dynamic load rating (C)	28,1 kN
Basic static load rating (C0)	32,5 kN