



Bearing No. 6822NR

f	1,7 mm
r	1
d	110 mm
D	140 mm
B	16 mm
C	16 mm
a	2,5 mm
b	1,9 mm
D2	145,7 mm
B_	16
Cy	3.9
ra	1
C0	32.5
fo	17.1
D_	140
D1	137,6 mm
rn	0,5 mm
Z_	25
Dx	147
ro	0.6
DE_	133.731
DA_	8.731
SRI	4.52
D_a	135
SRE	4.52
DI_	116.269
SRIN	-0.02
yobi	6822NR
SBRG	18
bomp	0

SREX	0.02
KBRG	6101
SREN	0
SDM_	125
SRIX	0.02
mass	0.497
C_conv	28100
r min.	1 mm
da max	117 mm
ALPHA_	0
Weight	0,497 Kg
da min	115
LangID	1
GRS rpm	4300
Da max.	135 mm
hidYobi	6822NR
Oil rpm	5300
da min.	115 mm
r0 max.	0,6 mm
ra max.	1 mm
hidTable	ecat_NSRDGB
Size (mm)	110x140x16
Prod_Type3	DGBB_SR_NR_OT
Width (mm)	16
Bearing number	6822NR
Bore Diameter (mm)	110
Outer Diameter (mm)	140
(Oil) Lubrication Speed	5 300 r/min
(Grease) Lubrication Speed	4 300 r/min
Basic dynamic load rating (C)	28,1 kN
Basic static load rating	32,5 kN

(C0)	
------	--