



Bearing No. 6332

r	4
d	160 mm
D	340 mm
B	68 mm
C	68 mm
fo	13.9
C0	287
ra	3
B_	68
Z_	8
D_	340
SRI	26.29
DA_	50.8
SRE	26.29
DE_	300.8
DI_	199.2
D_a	324
mass	26.2
SREN	-0.1
SRIN	-0.1
Bore	6.299 Inch 160 Millimeter
bomp	0
Noun	Bearing
yobi	6332
SRIX	0.1
SDM_	250
SREX	0.1
KBRG	6101
SBRG	3

C_conv	278000
ALPHA_	0
Weight	26,2 Kg
da max	215,5 mm
r min.	4 mm
da min	176
UNSPSC	31171504
LangID	1
hidYobi	6332
GRS rpm	1700
Oil rpm	2000
Da max.	324 mm
ra max.	3 mm
da min.	176 mm
Category	Single Row Ball Bearing
hidTable	ecat_NSRDGB
Size (mm)	160x340x68
Snap Ring	No
Enclosure	Open
Inventory	0.0
Width (mm)	68
Prod_Type3	DGBB_SR_OT
Weight / LBS	57.771
Inch - Metric	Metric
Cage Material	Steel
Product Group	B00308
Bearing number	6332
Keyword String	Ball
Other Features	Deep Groove
Rolling Element	Ball Bearing
Precision Class	ABEC 1 ISO P0
Inner Race Width	0 Inch 0 Millimeter

Long Description	160MM Bore; 340MM Outside Diameter; 68MM Outer Race Width; Open; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Cage
Outside Diameter	13.386 Inch 340 Millimeter
Outer Race Width	2.677 Inch 68 Millimeter
Manufacturer URL	http://www.nskamericas.com
Manufacturer Name	NSK
Weight / Kilogram	26
Internal Clearance	C0-Medium
Bore Diameter (mm)	160
Outer Diameter (mm)	340
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.68
(Oil) Lubrication Speed	2 000 r/min
Internal Special Features	No
(Grease) Lubrication Speed	1 700 r/min
Basic static load rating (C0)	287 kN
Basic dynamic load rating (C)	278 kN
Maximum Capacity / Filling Slot	No