



Bearing No. 6820LLB

D	125 mm
d	100 mm
B	13 mm
C	13 mm
Bore	3.937 Inch 100 Millimeter
Noun	Bearing
r min.	1 mm
Weight	0,313 Kg
UNSPSC	31171504
da max	106 mm
da min.	105 mm
Da max.	120 mm
ra max.	1 mm
Category	Single Row Ball Bearing
Snap Ring	No
Enclosure	2 Seals
Size (mm)	100x125x13
Inventory	0.0
bore type:	Round
Width (mm)	13
Weight / LBS	0.664
Product Group	B00308
Cage Material	Steel
closure type:	Double Sealed
Inch - Metric	Metric
bore diameter:	100 mm
overall width:	13 mm
Keyword String	Ball
cage material:	Steel

Other Features	Deep Groove Non-Friction Nitrile Rubber Seal Shell Alvania Prelubricated
Bearing number	6820LLB
Enclosure Type	Non-Contact Seal
Precision Class	ABEC 1 ISO P0
Rolling Element	Ball Bearing
Outside Diameter	4.921 Inch 125 Millimeter
Outer Race Width	0.512 Inch 13 Millimeter
Manufacturer URL	http://www.ntnamerica.com
Inner Race Width	0 Inch 0 Millimeter
Long Description	100MM Bore; 125MM Outside Diameter; 13MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Cage
outside diameter:	125 mm
Manufacturer Name	NTN
bearing material:	High Carbon Chrome Steel
Weight / Kilogram	0
Bore Diameter (mm)	100
Internal Clearance	C0-Medium
internal clearance:	CN
Outer Diameter (mm)	125
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.68
manufacturer upc	4547359586275

number:	
Internal Special Features	No
(Grease) Lubrication Speed	4 800 r/min
operating temperature range:	-40 to 250 °F °F
Basic static load rating (C0)	21,2 kN
Basic dynamic load rating (C)	19,6 kN
Maximum Capacity / Filling Slot	No