



Bearing No. 6817VV

r	1
d	85 mm
D	110 mm
B	13 mm
C	13 mm
D_	110
B_	13
ra	1
C0	20
fo	17.1
Z_	23
DI_	90.356
SRE	3.7
D_a	105
DE_	104.644
DA_	7.144
SRI	3.7
SREN	-0.02
SBRG	18
SREX	0.02
KBRG	6151
Bore	3.346 Inch 85 Millimeter
mass	0.263
Noun	Bearing
SRIX	0.02
SRIN	-0.02
SDM_	97.5
bomp	0
yobi	6817VV

Weight	0,263 Kg
LangID	1
da max	90,5 mm
C_conv	18700
ALPHA_	0
da min	90
UNSPSC	31171504
r min.	1 mm
hidYobi	6817VV
ra max.	1 mm
GRS rpm	5600
Da max.	105 mm
da min.	90 mm
hidTable	ecat_NSRDGB
Category	Single Row Ball Bearing
Snap Ring	No
Size (mm)	85x110x13
Enclosure	2 Seals
Inventory	0.0
Width (mm)	13
bore type:	Round
Prod_Type3	DGBB_SR_VV
Weight / LBS	0.32
Product Group	B00152
Cage Material	Steel
closure type:	Double Sealed
Inch - Metric	Metric
Bearing number	6817VV
Keyword String	Ball
overall width:	13 mm
Enclosure Type	Non-Contact Seal
bore diameter:	85 mm

Precision Class	ABEC 1 ISO P0
Rolling Element	Ball Bearing
Outer Race Width	0.512 Inch 13 Millimeter
Long Description	85MM Bore; 110MM Outside Diameter; 13MM Outer Race Diameter; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Outside Diameter	4.331 Inch 110 Millimeter
Manufacturer URL	http://www.nskamericas.com
Manufacturer Name	NSK
Weight / Kilogram	0.25
outside diameter:	110 mm
Bore Diameter (mm)	85
Internal Clearance	C0-Medium
Outer Diameter (mm)	110
internal clearance:	Normal Clearance
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.68
Manufacturer Item Number	6817VV
manufacturer upc number:	029176030321
Internal Special Features	No
(Grease) Lubrication Speed	5 600 r/min
Basic static load rating (C0)	20 kN
Basic dynamic load rating (C)	18,7 kN

Maximum Capacity / Filling Slot	No
------------------------------------	----