



### Bearing No. 635

D	19 mm
d	5 mm
B	6 mm
C	6 mm
Cr	2.90
f0	12.3
Cu	0.040
C0r	0.89
Bore	0.197 Inch   5 Millimeter
Noun	Bearing
r(min)	0.3
Weight	0,0085 Kg
UNSPSC	31171504
r min.	0,3 mm
r1 min.	0,3 mm
da min.	7 mm
ra max.	0,3 mm
da(min)	7
Da(max)	17
ra(max)	0.3
Da max.	17 mm
Oil lub.	43000
Category	Single Row Ball Bearing
Size (mm)	5x19x6
Snap Ring	No
Enclosure	Open
Inventory	0.0
Width (mm)	6
Bearing No.	635
Grease lub.	35000

Weight / LBS	0.0187
Product Group	B00308
Cage Material	Steel
Inch - Metric	Metric
Keyword String	Ball
Bearing number	635
Other Features	Deep Groove
Rolling Element	Ball Bearing
Precision Class	ABEC 1   ISO P0
(Refer.)Mass(g)	8.5
Manufacturer URL	<a href="http://www.koyousa.com">http://www.koyousa.com</a>
Inner Race Width	0 Inch   0 Millimeter
Outside Diameter	0.748 Inch   19 Millimeter
Long Description	5MM Bore; 19MM Outside Diameter; 6MM Outer Race Width; Open; Ball Bearing; ABEC 1   ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Cage
Outer Race Width	0.236 Inch   6 Millimeter
Manufacturer Name	KOYO
Weight / Kilogram	0
Internal Clearance	C0-Medium
Bore Diameter (mm)	5
Outer Diameter (mm)	19
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.68
(Oil) Lubrication Speed	43000 r/min
Internal Special Features	No
(Grease) Lubrication	35000 r/min

Speed	
Basic static load rating (C0)	1,05 kN
Basic dynamic load rating (C)	2,6 kN
Maximum Capacity / Filling Slot	No