



Bearing No. 6352 M

| | |
|-----------------------------------|-------------|
| D | 540 mm |
| d | 260 mm |
| B | 102 mm |
| Size (mm) | 540x260x102 |
| Width (mm) | 102 |
| Mass bearing | 115 kg |
| D ₁ | 445 mm |
| d ₁ | 356 mm |
| Limiting speed | 2200 r/min |
| Bearing number | 6352 M |
| Reference speed | 2400 r/min |
| r _a max. | 5 mm |
| D _a max. | 514 mm |
| Bore Diameter (mm) | 540 |
| d _a min. | 286 mm |
| Outer Diameter (mm) | 260 |
| D _a - max. | 514 mm |
| r _a - max. | 5 mm |
| r _{1,2} min. | 6 mm |
| d _a - min. | 286 mm |
| d ₁ ? | 358 mm |
| D ₁ ? | 442 mm |
| r _{1,2} - min. | 6 mm |
| Basic dynamic load rating C | 507 kN |
| Basic dynamic load rating - C | 507 kN |
| Fatigue load limit P _u | 15 kN |
| Calculation factor k _r | 0.03 |
| Calculation factor f ₀ | 14.6 |
| | |

| | |
|-------------------------------------|--------|
| Calculation factor - f_0 | 15 |
| Calculation factor - k_r | 0.03 |
| Fatigue load limit - P_u | 15 kN |
| Basic static load rating C_0 | 710 kN |
| Basic static load rating - C_0 | 710 kN |