



### Bearing No. 6815VV

r	0.6
d	75 mm
D	95 mm
B	10 mm
C	10 mm
D_	95
B_	10
ra	0.6
C0	13.9
fo	17.3
Z_	26
DI_	79.444
SRE	2.88
D_a	91
DE_	90.556
DA_	5.556
SRI	2.88
SREN	-0.015
SBRG	18
SREX	0.015
KBRG	6151
Bore	2.953 Inch   75 Millimeter
mass	0.149
Noun	Bearing
SRIX	0.015
SRIN	-0.015
SDM_	85
bomp	0
yobi	6815VV

Weight	0,149 Kg
LangID	1
da max	79,5 mm
C_conv	12500
ALPHA_	0
da min	79
UNSPSC	31171504
r min.	0,6 mm
hidYobi	6815VV
ra max.	0,6 mm
GRS rpm	6300
Da max.	91 mm
da min.	79 mm
hidTable	ecat_NSRDGB
Category	Single Row Ball Bearing
Snap Ring	No
Size (mm)	75x95x10
Enclosure	2 Seals
Inventory	0.0
Width (mm)	10
bore type:	Round
Prod_Type3	DGBB_SR_VV
Weight / LBS	0.14
Product Group	B00308
Cage Material	Steel
closure type:	Double Sealed
Inch - Metric	Metric
Bearing number	6815VV
Keyword String	Ball
overall width:	10 mm
Enclosure Type	Non-Contact Seal
bore diameter:	75 mm

Precision Class	ABEC 1   ISO P0
Rolling Element	Ball Bearing
Outside Diameter	3.74 Inch   95 Millimeter
Long Description	75MM Bore; 95MM Outside Diameter; 10MM Outer Race Diameter; 2 Seals; Ball Bearing; ABEC 1   ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Outer Race Width	0.394 Inch   10 Millimeter
Manufacturer URL	<a href="http://www.nskamericas.com">http://www.nskamericas.com</a>
Manufacturer Name	NSK
Weight / Kilogram	0.06
outside diameter:	95 mm
Bore Diameter (mm)	75
Internal Clearance	C0-Medium
Outer Diameter (mm)	95
internal clearance:	Normal Clearance
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.68
Manufacturer Item Number	6815VV
manufacturer upc number:	029176026683
Internal Special Features	No
(Grease) Lubrication Speed	6 300 r/min
Basic static load rating (C0)	13,9 kN
Basic dynamic load rating (C)	12,5 kN
Maximum Capacity /	No

Filling Slot	
--------------	--