



Bearing No. 6815ZZ

D	95 mm
d	75 mm
B	10 mm
C	10 mm
Noun	Bearing
Bore	2.953 Inch 75 Millimeter
Width	10 mm
UNSPSC	31171504
r min.	0.6 mm
Weight	0.145 Kg
da min.	79 mm
Da max.	91 mm
ra max.	0.6 mm
Category	Single Row Ball Bearing
ra (max)	0.6 mm
Da (max)	91 mm
da (min)	79 mm
Factor fo	16.0
Inventory	0.0
Bore Size	75 mm
Bore Type	Cylindrical Bore
Enclosure	2 Metal Shields
Snap Ring	No
Size (mm)	75x95x10
Width (mm)	10
Configuration	Single Row
Product Group	B00308
Cage Material	Steel
Inch - Metric	Metric

Other Features	Deep Groove
Keyword String	Ball
Bearing number	6815ZZ
Precision Class	ABEC 1 ISO P0
Rolling Element	Ball Bearing
Long Description	75MM Bore; 95MM Outside Diameter; 10MM Outer Race Width; 2 Metal Shields; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Stee
Manufacturer URL	http://www.nachiamerica.com
Outside Diameter	3.74 Inch 95 Millimeter
Outer Race Width	0.394 Inch 10 Millimeter
Inner Race Width	0 Inch 0 Millimeter
Radial Clearance	0.010 to 0.030 mm
Weight / Kilogram	0.145
Manufacturer Name	NACHI
Bore Diameter (mm)	75
Internal Clearance	C0-Medium
Static Load Rating	12,800 N
Dynamic Load Rating	12,500 N
Outer Diameter (mm)	95
Minimum Buy Quantity	N/A
Fillet Radius/Chamfer	0.6 mm
Harmonized Tariff Code	8482.10.50.68
Limiting Speed - Grease	6,500 rpm
Internal Special Features	No
Basic dynamic load	12,5 kN

rating (C)	
Basic static load rating (C0)	12,8 kN
Maximum Capacity / Filling Slot	No