



Bearing No. 6815ZZ

D	95 mm
d	75 mm
B	10 mm
C	10 mm
r	0.6
Z_	26
B_	10
D_	95
ra	0.6
C0	13.9
fo	17.3
DI_	79.444
SRI	2.88
D_a	91
DE_	90.556
DA_	5.556
SRE	2.88
SRIN	-0.015
SBRG	18
yobi	6815ZZ
SDM_	85
SREX	0.015
KBRG	6141
bomp	0
mass	0.149
Bore	2.953 Inch 75 Millimeter
SRIX	0.015
SREN	-0.015
Noun	Bearing

ALPHA_	0
da min	79
LangID	1
r min.	0,6 mm
UNSPSC	31171504
da max	79,5 mm
C_conv	12500
Weight	0,149 Kg
ra max.	0,6 mm
hidYobi	6815ZZ
GRS rpm	6300
Da max.	91 mm
da min.	79 mm
Category	Single Row Ball Bearing
hidTable	ecat_NSRDGB
Snap Ring	No
Size (mm)	75x95x10
Enclosure	2 Metal Shields
Inventory	0.0
Width (mm)	10
Prod_Type3	DGBB_SR_ZZ
Weight / LBS	0.3285
Cage Material	Steel
Inch - Metric	Metric
Product Group	B00308
Bearing number	6815ZZ
Keyword String	Ball
Other Features	Deep Groove
Precision Class	ABEC 1 ISO P0
Rolling Element	Ball Bearing
Outside Diameter	3.74 Inch 95 Millimeter
Inner Race Width	0 Inch 0 Millimeter

Long Description	75MM Bore; 95MM Outside Diameter; 10MM Outer Race Width; 2 Metal Shields; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Stee
Manufacturer URL	http://www.nskamericas.com
Outer Race Width	0.394 Inch 10 Millimeter
Weight / Kilogram	0.14
Manufacturer Name	NSK
Internal Clearance	C0-Medium
Bore Diameter (mm)	75
Outer Diameter (mm)	95
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.68
Internal Special Features	No
(Grease) Lubrication Speed	6 300 r/min
Basic static load rating (C0)	13,9 kN
Basic dynamic load rating (C)	12,5 kN
Maximum Capacity / Filling Slot	No