



Bearing No. 6815LLB

D	95 mm
d	75 mm
B	10 mm
C	10 mm
Bore	2.953 Inch 75 Millimeter
Noun	Bearing
da max	80 mm
UNSPSC	31171504
Weight	0,145 Kg
r min.	0,6 mm
da min.	79 mm
Da max.	91 mm
ra max.	0,6 mm
series:	68
Category	Single Row Ball Bearing
Inventory	0.0
Size (mm)	75x95x10
Enclosure	2 Seals
Snap Ring	No
bore type:	Round
Width (mm)	10
Weight / LBS	0.317
maximum rpm:	6400 RPM
closure type:	Double Sealed
Product Group	B00308
Cage Material	Steel
Inch - Metric	Metric
Other Features	Deep Groove Non-Friction Nitrile Rubber Seal Shell Alvania

	Prelubricated
Enclosure Type	Non-Contact Seal
Keyword String	Ball
Bearing number	6815LLB
bore diameter:	75 mm
overall width:	10 mm
cage material:	Steel
fillet radius:	0.6 mm
Rolling Element	Ball Bearing
Precision Class	ABEC 1 ISO P0
finish/coating:	Uncoated
Outside Diameter	3.74 Inch 95 Millimeter
Outer Race Width	0.394 Inch 10 Millimeter
Inner Race Width	0 Inch 0 Millimeter
Long Description	75MM Bore; 95MM Outside Diameter; 10MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Cage;
Manufacturer URL	http://www.ntnamerica.com
Weight / Kilogram	0
outer ring width:	10 mm
Manufacturer Name	NTN
bearing material:	High Carbon Chrome Steel
inner ring width:	10 mm
outside diameter:	95 mm
precision rating:	ISO Class 0
Internal Clearance	C0-Medium

Bore Diameter (mm)	75
Outer Diameter (mm)	95
internal clearance:	CN
snap ring included:	Without Snap Ring
Minimum Buy Quantity	N/A
row type & fill slot:	Single Row Non-Fill Slot
maximum rpm (grease):	6400 rpm
static load capacity:	12900 N
Harmonized Tariff Code	8482.10.50.68
dynamic load capacity:	12500 N
Internal Special Features	No
(Grease) Lubrication Speed	6 400 r/min
manufacturer product page:	Click here
operating temperature range:	-40 to 120 °C
Basic static load rating (C0)	12,9 kN
Basic dynamic load rating (C)	12,5 kN
Maximum Capacity / Filling Slot	No