



### Bearing No. 6815LLU

D	95 mm
d	75 mm
B	10 mm
C	10 mm
Noun	Bearing
Bore	2.953 Inch   75 Millimeter
da max	80 mm
UNSPSC	31171504
r min.	0,6 mm
Weight	0,145 Kg
da min.	79 mm
Da max.	91 mm
ra max.	0,6 mm
Category	Single Row Ball Bearing
Inventory	0.0
Enclosure	2 Seals
Size (mm)	75x95x10
Snap Ring	No
bore type:	Round
Width (mm)	10
Weight / LBS	0.314
Inch - Metric	Metric
closure type:	Double Sealed
Product Group	B00308
Cage Material	Steel
Other Features	Deep Groove   Double Lip Friction Nitrile Rubber Seal   -20 To 120 Deg C   Shell Alvania Prelubricated
bore diameter:	75 mm

Keyword String	Ball
overall width:	10 mm
cage material:	Steel
fillet radius:	0.6 mm
Bearing number	6815LLU
Enclosure Type	Contact Seal
Rolling Element	Ball Bearing
Reference speed	3 600 r/min
finish/coating:	Uncoated
Precision Class	ABEC 1   ISO P0
Manufacturer URL	<a href="http://www.ntnamerica.com">http://www.ntnamerica.com</a>
Outer Race Width	0.394 Inch   10 Millimeter
Outside Diameter	3.74 Inch   95 Millimeter
Inner Race Width	0 Inch   0 Millimeter
Long Description	75MM Bore; 95MM Outside Diameter; 10MM Outer Race Diameter; 2 Seals; Ball Bearing; ABEC 1   ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
outer ring width:	10 mm
inner ring width:	10 mm
bearing material:	High Carbon Chrome Steel
precision rating:	ISO Class 0
Weight / Kilogram	0.142
Manufacturer Name	NTN
outside diameter:	95 mm
Bore Diameter (mm)	75
Internal Clearance	C0-Medium
snap ring included:	Without Snap Ring

Outer Diameter (mm)	95
internal clearance:	CN
Minimum Buy Quantity	N/A
static load capacity:	12900 N
row type & fill slot:	Single Row Non-Fill Slot
maximum rpm (grease):	3600 rpm
Harmonized Tariff Code	8482.10.50.68
dynamic load capacity:	12500 N
Manufacturer Item Number	6815LLU/2AS
Internal Special Features	No
manufacturer product page:	<a href="#">Click here</a>
operating temperature range:	-40 to 120 °C
Basic static load rating (C0)	12,9 kN
Basic dynamic load rating (C)	12,5 kN
Maximum Capacity / Filling Slot	No