



Bearing No. 637

| | |
|----------------------------|-------------|
| D | 26 mm |
| d | 7 mm |
| B | 9 mm |
| C | 9 mm |
| Cu | 0.100 |
| f0 | 12.3 |
| Cr | 5.65 |
| C0r | 1.95 |
| r(min) | 0.3 |
| r min. | 0,3 mm |
| Weight | 0,024 Kg |
| da(min) | 9 |
| Da max. | 24 mm |
| ra max. | 0,3 mm |
| da min. | 9 mm |
| r1 min. | 0,3 mm |
| Da(max) | 24 |
| ra(max) | 0.3 |
| Oil lub. | 32000 |
| Size (mm) | 7x26x9 |
| Width (mm) | 9 |
| Grease lub. | 26000 |
| Bearing No. | 637 |
| Bearing number | 637 |
| (Refer.)Mass(g) | 24 |
| Bore Diameter (mm) | 7 |
| Outer Diameter (mm) | 26 |
| (Oil) Lubrication Speed | 32000 r/min |
| (Grease) Lubrication Speed | 26000 r/min |
| | |

| | |
|-------------------------------|---------|
| Basic static load rating (C0) | 1,95 kN |
| Basic dynamic load rating (C) | 4,55 kN |