



Bearing No. 6813VV

r	0.6
d	65 mm
D	85 mm
B	10 mm
C	10 mm
D_	85
B_	10
ra	0.6
C0	12.1
fo	17
Z_	23
DI_	69.444
SRE	2.88
D_a	81
DE_	80.556
DA_	5.556
SRI	2.88
SREN	-0.015
SBRG	18
SREX	0.015
KBRG	6151
Bore	2.559 Inch 65 Millimeter
mass	0.128
Noun	Bearing
SRIX	0.015
SRIN	-0.015
SDM_	75
bomp	0
yobi	6813VV

Weight	0,128 Kg
da min	69
LangID	1
da max	69 mm
C_conv	11900
ALPHA_	0
UNSPSC	31171504
r min.	0,6 mm
hidYobi	6813VV
ra max.	0,6 mm
GRS rpm	7500
Da max.	81 mm
da min.	69 mm
hidTable	ecat_NSRDGB
Category	Single Row Ball Bearing
Snap Ring	No
Size (mm)	65x85x10
Enclosure	2 Seals
Inventory	1.0
Width (mm)	10
bore type:	Round
Prod_Type3	DGBB_SR_VV
Weight / LBS	0.13
Product Group	B00308
Cage Material	Steel
closure type:	Double Sealed
Inch - Metric	Metric
Bearing number	6813VV
Keyword String	Ball
overall width:	10 mm
Enclosure Type	Non-Contact Seal
bore diameter:	65 mm

Precision Class	ABEC 1 ISO P0
Rolling Element	Ball Bearing
Outer Race Width	0.394 Inch 10 Millimeter
Long Description	65MM Bore; 85MM Outside Diameter; 10MM Outer Race Diameter; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Outside Diameter	3.346 Inch 85 Millimeter
Manufacturer URL	http://www.nskamericas.com
Manufacturer Name	NSK
Weight / Kilogram	0.06
outside diameter:	85 mm
Bore Diameter (mm)	65
Internal Clearance	C0-Medium
Outer Diameter (mm)	85
internal clearance:	Normal Clearance
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.68
Manufacturer Item Number	6813VV
manufacturer upc number:	029176030307
Internal Special Features	No
(Grease) Lubrication Speed	7 500 r/min
Basic static load rating (C0)	12,1 kN
Basic dynamic load rating (C)	11,9 kN

Maximum Capacity / Filling Slot	No
------------------------------------	----