



Bearing No. 6813ZZ

D	85 mm
d	65 mm
B	10 mm
C	10 mm
r	0.6
Z_	23
B_	10
D_	85
ra	0.6
C0	12.1
fo	17
DI_	69.444
SRI	2.88
D_a	81
DE_	80.556
DA_	5.556
SRE	2.88
SRIN	-0.015
SBRG	18
yobi	6813ZZ
SDM_	75
SREX	0.015
KBRG	6141
bomp	0
mass	0.128
Bore	2.559 Inch 65 Millimeter
SRIX	0.015
SREN	-0.015
Noun	Bearing

ALPHA_	0
da min	69
LangID	1
r min.	0,6 mm
UNSPSC	31171504
da max	69 mm
C_conv	11900
Weight	0,128 Kg
ra max.	0,6 mm
hidYobi	6813ZZ
GRS rpm	7500
Da max.	81 mm
da min.	69 mm
Category	Single Row Ball Bearing
hidTable	ecat_NSRDGB
Snap Ring	No
Size (mm)	65x85x10
Enclosure	2 Metal Shields
Inventory	0.0
Width (mm)	10
Prod_Type3	DGBB_SR_ZZ
Weight / LBS	0.2822
Cage Material	Steel
Inch - Metric	Metric
Product Group	B00308
Bearing number	6813ZZ
Keyword String	Ball
Other Features	Deep Groove
Precision Class	ABEC 1 ISO P0
Rolling Element	Ball Bearing
Outer Race Width	0.394 Inch 10 Millimeter
Inner Race Width	0 Inch 0 Millimeter

Long Description	65MM Bore; 85MM Outside Diameter; 10MM Outer Race Width; 2 Metal Shields; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Stee
Manufacturer URL	http://www.nskamericas.com
Outside Diameter	3.346 Inch 85 Millimeter
Weight / Kilogram	0.12
Manufacturer Name	NSK
Internal Clearance	C0-Medium
Bore Diameter (mm)	65
Outer Diameter (mm)	85
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.68
Internal Special Features	No
(Grease) Lubrication Speed	7 500 r/min
Basic static load rating (C0)	12,1 kN
Basic dynamic load rating (C)	11,9 kN
Maximum Capacity / Filling Slot	No