



Bearing No. 6813ZZ

D	85 mm
d	65 mm
B	10 mm
C	10 mm
rn	0,5 mm
Noun	Bearing
Bore	2.559 Inch 65 Millimeter
UNSPSC	31171504
da max	70 mm
Weight	0,128 Kg
r min.	0,6 mm
da min.	69 mm
Da max.	81 mm
ra max.	0,6 mm
series:	68
Category	Single Row Ball Bearing
Enclosure	2 Metal Shields
Size (mm)	65x85x10
Inventory	0.0
Snap Ring	No
Width (mm)	10
bore type:	Round
Weight / LBS	0.26
maximum rpm:	7400 RPM
closure type:	Double Shielded
Product Group	B00308
Inch - Metric	Metric
Cage Material	Steel
Keyword String	Ball

Other Features	Deep Groove Shell Alvania Prelubricated
Bearing number	6813ZZ
bore diameter:	65 mm
overall width:	10 mm
cage material:	Steel
fillet radius:	0.6 mm
Rolling Element	Ball Bearing
Precision Class	ABEC 1 ISO P0
finish/coating:	Uncoated
Outer Race Width	0.394 Inch 10 Millimeter
Outside Diameter	3.346 Inch 85 Millimeter
Inner Race Width	0 Inch 0 Millimeter
Long Description	65MM Bore; 85MM Outside Diameter; 10MM Outer Race Width; 2 Metal Shields; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Stee
Manufacturer URL	http://www.ntnamerica.com
Weight / Kilogram	0
outer ring width:	10 mm
Manufacturer Name	NTN
bearing material:	High Carbon Chrome Steel
inner ring width:	10 mm
outside diameter:	85 mm
precision rating:	ISO Class 0
Internal Clearance	C0-Medium

Bore Diameter (mm)	65
Outer Diameter (mm)	85
internal clearance:	CN
snap ring included:	Without Snap Ring
Minimum Buy Quantity	N/A
row type & fill slot:	Single Row Non-Fill Slot
maximum rpm (grease):	7400 rpm
static load capacity:	11000 N
Harmonized Tariff Code	8482.10.50.68
dynamic load capacity:	11600 N
Internal Special Features	No
(Grease) Lubrication Speed	7 400 r/min
manufacturer product page:	Click here
operating temperature range:	-40 to 120 °C
Basic static load rating (C0)	11 kN
Basic dynamic load rating (C)	11,6 kN
Maximum Capacity / Filling Slot	No