



Bearing No. 6812N

a	1,7 mm
r	0.3
d	60 mm
D	78 mm
B	10 mm
C	10 mm
b	1,3 mm
fo	16.9
B_	10
ra	0.3
C0	10.9
D1	76,2 mm
D_	78
Z_	21
rn	0,3 mm
ro	0.4
DE_	74.556
SRI	2.88
D_a	76
DA_	5.556
SRE	2.88
DI_	63.444
yobi	6812N
mass	0.103
SBRG	18
bomp	0
KBRG	6101
SREX	0.015
SREN	-0.015
SRIN	-0.015

SDM_	69
SRIX	0.015
ALPHA_	0
r min.	0,3 mm
C_conv	11500
da max	64 mm
da min	62
Weight	0,103 Kg
LangID	1
ra max.	0,3 mm
Da max.	76 mm
Oil rpm	9500
da min.	62 mm
r0 max.	0,4 mm
hidYobi	6812N
GRS rpm	8000
hidTable	ecat_NSRDGB
Size (mm)	60x78x10
Prod_Type3	DGBB_SR_N_OT
Width (mm)	10
Bearing number	6812N
Bore Diameter (mm)	60
Outer Diameter (mm)	78
(Oil) Lubrication Speed	9 500 r/min
(Grease) Lubrication Speed	8 000 r/min
Basic dynamic load rating (C)	11,5 kN
Basic static load rating (C0)	10,9 kN