



Bearing No. 6812VV

r	0.3
d	60 mm
D	78 mm
B	10 mm
C	10 mm
D_	78
B_	10
ra	0.3
C0	10.9
fo	16.9
Z_	21
DI_	63.444
SRE	2.88
D_a	76
DE_	74.556
DA_	5.556
SRI	2.88
SREN	-0.015
SBRG	18
SREX	0.015
KBRG	6151
Bore	2.362 Inch 60 Millimeter
mass	0.103
Noun	Bearing
SRIX	0.015
SRIN	-0.015
SDM_	69
bomp	0
yobi	6812VV

Weight	0,103 Kg
LangID	1
da max	64 mm
C_conv	11500
ALPHA_	0
da min	62
UNSPSC	31171504
r min.	0,3 mm
hidYobi	6812VV
ra max.	0,3 mm
GRS rpm	8000
Da max.	76 mm
da min.	62 mm
hidTable	ecat_NSRDGB
Category	Single Row Ball Bearing
Snap Ring	No
Size (mm)	60x78x10
Enclosure	2 Seals
Inventory	0.0
Width (mm)	10
bore type:	Round
Prod_Type3	DGBB_SR_VV
Weight / LBS	0.13
Product Group	B00308
Cage Material	Steel
closure type:	Double Sealed
Inch - Metric	Metric
Bearing number	6812VV
Keyword String	Ball
overall width:	10 mm
Enclosure Type	Non-Contact Seal
bore diameter:	60 mm

Precision Class	ABEC 1 ISO P0
Rolling Element	Ball Bearing
Outside Diameter	3.071 Inch 78 Millimeter
Long Description	60MM Bore; 78MM Outside Diameter; 10MM Outer Race Diameter; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Outer Race Width	0.394 Inch 10 Millimeter
Manufacturer URL	http://www.nskamericas.com
Manufacturer Name	NSK
Weight / Kilogram	0.06
outside diameter:	78 mm
Bore Diameter (mm)	60
Internal Clearance	C0-Medium
Outer Diameter (mm)	78
internal clearance:	Normal Clearance
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.68
Manufacturer Item Number	6812VV
manufacturer upc number:	029176030291
Internal Special Features	No
(Grease) Lubrication Speed	8 000 r/min
Basic static load rating (C0)	10,9 kN
Basic dynamic load rating (C)	11,5 kN

Maximum Capacity / Filling Slot	No
------------------------------------	----