



Bearing No. 6812DD

r	0.3
d	60 mm
D	78 mm
B	10 mm
C	10 mm
fo	16.9
D_	78
B_	10
ra	0.3
Z_	21
C0	10.9
DI_	63.444
SRE	2.88
D_a	76
DE_	74.556
SRI	2.88
DA_	5.556
SREN	-0.015
Bore	2.362 Inch 60 Millimeter
SRIN	-0.015
bomp	0
SRIX	0.015
yobi	6812DD
mass	0.103
SDM_	69
KBRG	6191
SREX	0.015
SBRG	18
Noun	Bearing

da max	64 mm
Weight	0,103 Kg
LangID	1
r min.	0,3 mm
da min	62
ALPHA_	0
C_conv	11500
UNSPSC	31171504
da min.	62 mm
hidYobi	6812DD
GRS rpm	4500
Da max.	76 mm
ra max.	0,3 mm
Category	Single Row Ball Bearing
hidTable	ecat_NSRDGB
Snap Ring	No
Enclosure	2 Seals
Size (mm)	60x78x10
Inventory	0.0
Prod_Type3	DGBB_SR_DD
Width (mm)	10
Weight / LBS	0.2271
Product Group	B00308
Inch - Metric	Metric
Cage Material	Steel
Bearing number	6812DD
Enclosure Type	Contact Seal
Other Features	Deep Groove
Keyword String	Ball
Rolling Element	Ball Bearing
Precision Class	ABEC 1 ISO P0
Outside Diameter	3.071 Inch 78 Millimeter

Inner Race Width	0 Inch 0 Millimeter
Long Description	60MM Bore; 78MM Outside Diameter; 10MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Cage;
Manufacturer URL	http://www.nskamericas.com
Outer Race Width	0.394 Inch 10 Millimeter
Weight / Kilogram	0.1
Manufacturer Name	NSK
Internal Clearance	C0-Medium
Bore Diameter (mm)	60
Outer Diameter (mm)	78
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.68
Internal Special Features	No
(Grease) Lubrication Speed	4 500 r/min
Basic dynamic load rating (C)	11,5 kN
Basic static load rating (C0)	10,9 kN
Maximum Capacity / Filling Slot	No