



Bearing No. 6811LLU

C	9 mm
d	55 mm
D	72 mm
B	9 mm
Bore	2.165 Inch 55 Millimeter
Noun	Bearing
Weight	0,083 Kg
da max	59 mm
UNSPSC	31171504
r min.	0,3 mm
da min.	57 mm
ra max.	0,3 mm
series:	68
Da max.	70 mm
Category	Single Row Ball Bearing
Enclosure	2 Seals
Size (mm)	55x72x9
Inventory	0.0
Snap Ring	No
Width (mm)	9
bore type:	Round
maximum rpm:	4800 RPM
Weight / LBS	0.179
Cage Material	Steel
Inch - Metric	Metric
closure type:	Double Sealed
Product Group	B00308
bore diameter:	55 mm
Keyword String	Ball

overall width:	9 mm
cage material:	Steel
fillet radius:	0.3 mm
Bearing number	6811LLU
Enclosure Type	Contact Seal
Reference speed	4 800 r/min
finish/coating:	Uncoated
Rolling Element	Ball Bearing
Precision Class	ABEC 1 ISO P0
Outer Race Width	0.354 Inch 9 Millimeter
Manufacturer URL	http://www.ntnamerica.com
Long Description	55MM Bore; 72MM Outside Diameter; 9MM Outer Race Diameter; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Outside Diameter	2.835 Inch 72 Millimeter
outside diameter:	72 mm
precision rating:	ISO Class 0
bearing material:	High Carbon Chrome Steel
Weight / Kilogram	0.081
inner ring width:	9 mm
outer ring width:	9 mm
Manufacturer Name	NTN
Bore Diameter (mm)	55
Internal Clearance	C0-Medium
internal clearance:	CN
snap ring included:	Without Snap Ring
Outer Diameter (mm)	72

Minimum Buy Quantity	N/A
row type & fill slot:	Single Row Non-Fill Slot
maximum rpm (grease):	4800 rpm
static load capacity:	8100 N
dynamic load capacity:	8800 N
Harmonized Tariff Code	8482.10.50.68
Manufacturer Item Number	6811JRLLU/2AS
Internal Special Features	No
manufacturer product page:	Click here
operating temperature range:	-40 to 120 °C
Basic static load rating (C0)	8,1 kN
Basic dynamic load rating (C)	8,8 kN
Maximum Capacity / Filling Slot	No