



**Bearing No. 6403ZZ**

D	62,000 mm
C	17,000 mm
B	17,000 mm
d	17,000 mm
Bore	0.669 Inch   17 Millimeter
Noun	Bearing
UNSPSC	31171504
series:	64
Category	Single Row Ball Bearing
Size (mm)	17x62x17
Enclosure	2 Metal Shields
Snap Ring	No
Inventory	0.0
Width (mm)	17,000
bore type:	Round
maximum rpm:	16000 RPM
Weight / LBS	0.595
Cage Material	Steel
closure type:	Double Shielded
Product Group	B00308
Inch - Metric	Metric
Bearing number	6403ZZ
bore diameter:	17 mm
overall width:	17 mm
fillet radius:	1.1 mm
cage material:	Steel
Keyword String	Ball
Rolling Element	Ball Bearing
finish/coating:	Uncoated

Precision Class	ABEC 1   ISO P0
Manufacturer URL	<a href="http://www.ntnamerica.com">http://www.ntnamerica.com</a>
Long Description	17MM Bore; 62MM Outside Diameter; 17MM Outer Race Diameter; 2 Metal Shields; Ball Bearing; ABEC 1   ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Outside Diameter	2.441 Inch   62 Millimeter
Outer Race Width	0.669 Inch   17 Millimeter
Weight / Kilogram	0.269
outer ring width:	17 mm
inner ring width:	17 mm
bearing material:	High Carbon Chrome Steel
Manufacturer Name	NTN
outside diameter:	62 mm
precision rating:	ISO Class 0
Bore Diameter (mm)	17,000
Internal Clearance	C0-Medium
Outer Diameter (mm)	62,000
snap ring included:	Without Snap Ring
internal clearance:	CN
Minimum Buy Quantity	N/A
row type & fill slot:	Single Row Non-Fill Slot
static load capacity:	10800 N
maximum rpm (grease):	14000 rpm
dynamic load capacity:	22700 N
Harmonized Tariff Code	8482.10.50.68
Manufacturer Item	6403ZZ/2A

Number	
Internal Special Features	No
manufacturer product page:	<a href="#">Click here</a>
operating temperature range:	-40 to 120 °C
Maximum Capacity / Filling Slot	No