



Bearing No. 6404

D	72 mm
d	20 mm
B	19 mm
C	19 mm
f0	11.1
Cu	1.50
Cr	38.7
C0r	15.2
Bore	0.787 Inch 20 Millimeter
Noun	Bearing
UNSPSC	31171504
Weight	0,4 Kg
r(min)	1.1
r min.	1,1 mm
da min.	26,5 mm
ra(max)	1
Da max.	65,5 mm
Da(max)	65.5
da(min)	26.5
ra max.	1 mm
Category	Single Row Ball Bearing
Oil lub.	13000
Inventory	0.0
Enclosure	Open
Size (mm)	20x72x19
Snap Ring	No
Width (mm)	19
Grease lub.	11000
Bearing No.	6404

Weight / LBS	1.156
Product Group	B00308
Cage Material	Steel
Inch - Metric	Metric
Keyword String	Ball
Bearing number	6404
Precision Class	ABEC 1 ISO P0
Rolling Element	Ball Bearing
Outer Race Width	0.748 Inch 19 Millimeter
Long Description	20MM Bore; 72MM Outside Diameter; 19MM Outer Race Diameter; Open; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Outside Diameter	2.835 Inch 72 Millimeter
(Refer.)Mass(kg)	0.400
Manufacturer URL	http://www.koyousa.com
Weight / Kilogram	0.525
Manufacturer Name	KOYO
Internal Clearance	C0-Medium
Bore Diameter (mm)	20
Outer Diameter (mm)	72
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.68
(Oil) Lubrication Speed	13000 r/min
Manufacturer Item Number	6404
Internal Special Features	No
(Grease) Lubrication Speed	11000 r/min

Basic static load rating (C0)	15,2 kN
Basic dynamic load rating (C)	31 kN
Maximum Capacity / Filling Slot	No