



Bearing No. 6404ZZ

D	72,000 mm
d	20,000 mm
B	19,000 mm
C	19,000 mm
Noun	Bearing
Bore	0.787 Inch 20 Millimeter
UNSPSC	31171504
Category	Single Row Ball Bearing
Size (mm)	20x72x19
Snap Ring	No
Inventory	0.0
Enclosure	2 Metal Shields
bore type:	Round
Width (mm)	19,000
Weight / LBS	0.902
Product Group	B00308
closure type:	Double Shielded
Cage Material	Steel
Inch - Metric	Metric
overall width:	19 mm
bore diameter:	20 mm
cage material:	Steel
Keyword String	Ball
fillet radius:	1.1 mm
Bearing number	6404ZZ
finish/coating:	Uncoated
Rolling Element	Ball Bearing
Precision Class	ABEC 1 ISO P0
Outer Race Width	0.748 Inch 19 Millimeter

Outside Diameter	2.835 Inch 72 Millimeter
Long Description	20MM Bore; 72MM Outside Diameter; 19MM Outer Race Diameter; 2 Metal Shields; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Manufacturer URL	http://www.ntnamerica.com
Manufacturer Name	NTN
outer ring width:	19 mm
outside diameter:	72 mm
precision rating:	ISO Class 0
Weight / Kilogram	0.408
inner ring width:	19 mm
bearing material:	High Carbon Chrome Steel
Bore Diameter (mm)	20,000
Internal Clearance	C0-Medium
snap ring included:	Without Snap Ring
Outer Diameter (mm)	72,000
internal clearance:	CN
Minimum Buy Quantity	N/A
row type & fill slot:	Single Row Non-Fill Slot
maximum rpm (grease):	12000 rpm
static load capacity:	13900 N
dynamic load capacity:	28500 N
Harmonized Tariff Code	8482.10.50.68
Manufacturer Item Number	6404ZZ/2AS
Internal Special Features	No

manufacturer product page:	Click here
operating temperature range:	-40 to 120 °C
Maximum Capacity / Filling Slot	No