



Bearing No. 6406

D	90 mm
d	30 mm
B	23 mm
C	23 mm
f0	12.3
Bore	1.181 Inch 30 Millimeter
Noun	Bearing
Mass	0.74 kg
Da max	82 mm
UNSPSC	31171504
r min.	1,5 mm
rs min	1.5 mm
da min	38 mm
Weight	0,735 Kg
ra max	1.5 mm
Da max.	82 mm
ra max.	1,5 mm
da min.	38 mm
series:	64
Category	Single Row Ball Bearing
Snap Ring	No
Inventory	0.0
Enclosure	Open
Size (mm)	30x90x23
Nlim (oil)	10,000 rpm
bore type:	Round
Width (mm)	23
Weight / LBS	1.616
maximum rpm:	10000 RPM

Nlim (grease)	8,800 rpm
Product Group	B00308
Inch - Metric	Metric
Cage Material	Steel
closure type:	Open
Keyword String	Ball
bore diameter:	30 mm
cage material:	Steel
fillet radius:	1.5 mm
overall width:	23 mm
Bearing number	6406
Dynamic load, C	43.5 kN
Precision Class	ABEC 1 ISO P0
Rolling Element	Ball Bearing
finish/coating:	Uncoated
Static load, C0	23.9 kN
Manufacturer URL	http://www.ntnamerica.com
Outside Diameter	3.543 Inch 90 Millimeter
Outer Race Width	0.906 Inch 23 Millimeter
Long Description	30MM Bore; 90MM Outside Diameter; 23MM Outer Race Diameter; Open; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
outer ring width:	23 mm
inner ring width:	23 mm
bearing material:	High Carbon Chrome Steel
outside diameter:	90 mm
Weight / Kilogram	0.732

precision rating:	Class 0
Manufacturer Name	NTN
maximum rpm (oil):	10000 rpm
Internal Clearance	C0-Medium
Bore Diameter (mm)	30
Outer Diameter (mm)	90
internal clearance:	CN
snap ring included:	Without Snap Ring
Minimum Buy Quantity	N/A
maximum rpm (grease):	8800 rpm
static load capacity:	23900 N
row type & fill slot:	Single Row Non-Fill Slot
Radial clearance class	CN
dynamic load capacity:	43500 N
Fatigue limit load, Cu	1.09 kN
Harmonized Tariff Code	8482.10.50.68
(Oil) Lubrication Speed	10 000 r/min
Manufacturer Item Number	6406
Internal Special Features	No
(Grease) Lubrication Speed	8 800 r/min
manufacturer product page:	Click here
operating temperature range:	-40 to 120 °C
Basic static load rating (C0)	23,9 kN
Basic dynamic load rating (C)	43,5 kN
Max operating temperature, Tmax	120 °C
Min operating temperature, Tmin	-20 °C

Maximum Capacity / Filling Slot	No
Characteristic cage frequency, FTF	0.36 Hz
Characteristic inner ring frequency, BPF1	4.45 Hz
Characteristic outer ring frequency, BPF0	2.55 Hz
Characteristic rolling element frequency, BSF	3.42 Hz