



Bearing No. 6406ZZ

D	90,000 mm
C	23,000 mm
B	23,000 mm
d	30,000 mm
Bore	1.181 Inch 30 Millimeter
Noun	Bearing
UNSPSC	31171504
series:	64
Category	Single Row Ball Bearing
Size (mm)	30x90x23
Enclosure	2 Metal Shields
Snap Ring	No
Inventory	0.0
Width (mm)	23,000
bore type:	Round
maximum rpm:	10000 RPM
Weight / LBS	1.629
Cage Material	Steel
closure type:	Double Shielded
Product Group	B00308
Inch - Metric	Metric
Bearing number	6406ZZ
bore diameter:	30 mm
overall width:	23 mm
fillet radius:	1.5 mm
cage material:	Steel
Keyword String	Ball
Rolling Element	Ball Bearing
finish/coating:	Uncoated

Precision Class	ABEC 1 ISO P0
Manufacturer URL	http://www.ntnamerica.com
Outside Diameter	3.543 Inch 90 Millimeter
Long Description	30MM Bore; 90MM Outside Diameter; 23MM Outer Race Diameter; 2 Metal Shields; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Outer Race Width	0.906 Inch 23 Millimeter
Weight / Kilogram	0.737
outer ring width:	23 mm
inner ring width:	23 mm
bearing material:	High Carbon Chrome Steel
Manufacturer Name	NTN
outside diameter:	90 mm
precision rating:	ISO Class 0
Bore Diameter (mm)	30,000
Internal Clearance	C0-Medium
Outer Diameter (mm)	90,000
snap ring included:	Without Snap Ring
internal clearance:	CN
Minimum Buy Quantity	N/A
row type & fill slot:	Single Row Non-Fill Slot
static load capacity:	23900 N
maximum rpm (grease):	8800 rpm
dynamic load capacity:	43500 N
Harmonized Tariff Code	8482.10.50.68
Manufacturer Item	6406ZZ/2AS

Number	
Internal Special Features	No
manufacturer product page:	Click here
operating temperature range:	-40 to 120 °C
Maximum Capacity / Filling Slot	No