



Bearing No. 6808DD

r	0.3
d	40 mm
D	52 mm
B	7 mm
C	7 mm
Z_	21
B_	7
D_	52
fo	17
ra	0.3
C0	5.55
DI_	42.031
DE_	49.969
DA_	3.969
D_a	50
SRI	2.05
SRE	2.05
Bore	1.575 Inch 40 Millimeter
SRIN	-0.015
Noun	Bearing
bomp	0
SREN	-0.015
SREX	0.015
SRIX	0.015
mass	0.031
KBRG	6191
SBRG	18
yobi	6808DD
SDM_	46

Weight	0,031 Kg
LangID	1
r min.	0,3 mm
ALPHA_	0
UNSPSC	31171504
da min	42
C_conv	6350
da max	42 mm
da min.	42 mm
GRS rpm	6700
hidYobi	6808DD
ra max.	0,3 mm
Da max.	50 mm
Category	Single Row Ball Bearing
hidTable	ecat_NSRDGB
Enclosure	2 Seals
Size (mm)	40x52x7
Inventory	0.0
Snap Ring	No
Width (mm)	7
Prod_Type3	DGBB_SR_DD
Weight / LBS	0.03
Product Group	B00308
Inch - Metric	Metric
Cage Material	Steel
Bearing number	6808DD
Keyword String	Ball
Rolling Element	Ball Bearing
Precision Class	ABEC 1 ISO P0
Manufacturer URL	http://www.nskamericas.com
Outer Race Width	0.276 Inch 7 Millimeter
Outside Diameter	2.047 Inch 52

	Millimeter
Long Description	40MM Bore; 52MM Outside Diameter; 7MM Outer Race Diameter; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Manufacturer Name	NSK
Weight / Kilogram	0.01
Internal Clearance	C0-Medium
Bore Diameter (mm)	40
Outer Diameter (mm)	52
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.68
Manufacturer Item Number	6808DD
Internal Special Features	No
(Grease) Lubrication Speed	6 700 r/min
Basic static load rating (C0)	5,55 kN
Basic dynamic load rating (C)	6,35 kN
Maximum Capacity / Filling Slot	No