



### Bearing No. 6808LLB

C	7 mm
d	40 mm
D	52 mm
B	7 mm
Bore	1.575 Inch   40 Millimeter
Noun	Bearing
Weight	0,033 Kg
da max	43 mm
UNSPSC	31171504
r min.	0,3 mm
da min.	42 mm
ra max.	0,3 mm
series:	68
Da max.	50 mm
Category	Single Row Ball Bearing
Enclosure	2 Seals
Size (mm)	40x52x7
Inventory	0.0
Snap Ring	No
Width (mm)	7
bore type:	Round
maximum rpm:	12000 RPM
Weight / LBS	0.065
Cage Material	Steel
Inch - Metric	Metric
closure type:	Double Sealed
Product Group	B00308
bore diameter:	40 mm
Keyword String	Ball

overall width:	7 mm
cage material:	Steel
fillet radius:	0.3 mm
Bearing number	6808LLB
Enclosure Type	Non-Contact Seal
Rolling Element	Ball Bearing
Precision Class	ABEC 1   ISO P0
finish/coating:	Uncoated
Long Description	40MM Bore; 52MM Outside Diameter; 7MM Outer Race Diameter; 2 Seals; Ball Bearing; ABEC 1   ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Manufacturer URL	<a href="http://www.ntnamerica.com">http://www.ntnamerica.com</a>
Outer Race Width	0.276 Inch   7 Millimeter
Outside Diameter	2.047 Inch   52 Millimeter
bearing material:	High Carbon Chrome Steel
outer ring width:	7 mm
inner ring width:	7 mm
Manufacturer Name	NTN
Weight / Kilogram	0.029
precision rating:	ISO Class 0
outside diameter:	52 mm
Bore Diameter (mm)	40
Internal Clearance	C0-Medium
snap ring included:	Without Snap Ring
Outer Diameter (mm)	52
internal clearance:	CN
Minimum Buy Quantity	N/A

static load capacity:	4400 N
maximum rpm (grease):	12000 rpm
row type & fill slot:	Single Row Non-Fill Slot
dynamic load capacity:	5100 N
Harmonized Tariff Code	8482.10.50.68
Manufacturer Item Number	6808JRLLB/2AS
Internal Special Features	No
(Grease) Lubrication Speed	12 000 r/min
manufacturer product page:	<a href="#">Click here</a>
operating temperature range:	-40 to 120 °C
Basic dynamic load rating (C)	5,1 kN
Basic static load rating (C0)	4,4 kN
Maximum Capacity / Filling Slot	No