



Bearing No. 6808N

a	1,3 mm
r	0.3
d	40 mm
D	52 mm
B	7 mm
C	7 mm
b	0,95 mm
fo	17
B_	7
ra	0.3
C0	5.55
D1	50,7 mm
D_	52
Z_	21
rn	0,3 mm
ro	0.25
DE_	49.969
SRI	2.05
D_a	50
DA_	3.969
SRE	2.05
DI_	42.031
yobi	6808N
mass	0.031
SBRG	18
bomp	0
KBRG	6101
SREX	0.015
SREN	-0.015
SRIN	-0.015

SDM_	46
SRIX	0.015
ALPHA_	0
r min.	0,3 mm
C_conv	6350
da max	42 mm
da min	42
Weight	0,031 Kg
LangID	1
ra max.	0,3 mm
Da max.	50 mm
Oil rpm	14000
da min.	42 mm
r0 max.	0,25 mm
hidYobi	6808N
GRS rpm	12000
hidTable	ecat_NSRDGB
Size (mm)	40x52x7
Prod_Type3	DGBB_SR_N_OT
Width (mm)	7
Bearing number	6808N
Bore Diameter (mm)	40
Outer Diameter (mm)	52
(Oil) Lubrication Speed	14 000 r/min
(Grease) Lubrication Speed	12 000 r/min
Basic dynamic load rating (C)	6,35 kN
Basic static load rating (C0)	5,55 kN