



Bearing No. 6808NR

f	0,85 mm
r	0.3
d	40 mm
D	52 mm
B	7 mm
C	7 mm
a	1,3 mm
b	0,95 mm
D2	54,8 mm
B_	7
Cy	1.8
ra	0.3
C0	5.55
fo	17
D_	52
D1	50,7 mm
rn	0,3 mm
Z_	21
Dx	55.5
ro	0.25
DE_	49.969
DA_	3.969
SRI	2.05
D_a	50
SRE	2.05
DI_	42.031
SRIN	-0.015
yobi	6808NR
SBRG	18
bomp	0

SREX	0.015
KBRG	6101
SREN	-0.015
SDM_	46
SRIX	0.015
mass	0.031
C_conv	6350
r min.	0,3 mm
da max	42 mm
ALPHA_	0
Weight	0,031 Kg
da min	42
LangID	1
GRS rpm	12000
Da max.	50 mm
hidYobi	6808NR
Oil rpm	14000
da min.	42 mm
r0 max.	0,25 mm
ra max.	0,3 mm
hidTable	ecat_NSRDGB
Size (mm)	40x52x7
Prod_Type3	DGBB_SR_NR_OT
Width (mm)	7
Bearing number	6808NR
Bore Diameter (mm)	40
Outer Diameter (mm)	52
(Oil) Lubrication Speed	14 000 r/min
(Grease) Lubrication Speed	12 000 r/min
Basic dynamic load rating (C)	6,35 kN
Basic static load rating	5,55 kN

(C0)	
------	--