



## Bearing No. 6808VV

r	0.3
d	40 mm
D	52 mm
B	7 mm
C	7 mm
D_	52
B_	7
ra	0.3
C0	5.55
fo	17
Z_	21
DI_	42.031
SRE	2.05
D_a	50
DE_	49.969
DA_	3.969
SRI	2.05
SREN	-0.015
SBRG	18
SREX	0.015
KBRG	6151
Bore	1.575 Inch   40 Millimeter
mass	0.031
Noun	Bearing
SRIX	0.015
SRIN	-0.015
SDM_	46
bomp	0
yobi	6808VV

Weight	0,031 Kg
LangID	1
da max	42 mm
C_conv	6350
ALPHA_	0
da min	42
UNSPSC	31171504
r min.	0,3 mm
hidYobi	6808VV
ra max.	0,3 mm
GRS rpm	12000
Da max.	50 mm
da min.	42 mm
hidTable	ecat_NSRDGB
Category	Single Row Ball Bearing
Snap Ring	No
Size (mm)	40x52x7
Enclosure	2 Seals
Inventory	0.0
Width (mm)	7
bore type:	Round
Prod_Type3	DGBB_SR_VV
Weight / LBS	0.035
Product Group	B00308
Cage Material	Steel
closure type:	Double Sealed
Inch - Metric	Metric
Bearing number	6808VV
Keyword String	Ball
overall width:	7 mm
Enclosure Type	Non-Contact Seal
bore diameter:	40 mm

Precision Class	ABEC 1   ISO P0
Rolling Element	Ball Bearing
Outer Race Width	0.276 Inch   7 Millimeter
Long Description	40MM Bore; 52MM Outside Diameter; 7MM Outer Race Diameter; 2 Seals; Ball Bearing; ABEC 1   ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Outside Diameter	2.047 Inch   52 Millimeter
Manufacturer URL	<a href="http://www.nskamericas.com">http://www.nskamericas.com</a>
Manufacturer Name	NSK
Weight / Kilogram	0.02
outside diameter:	52 mm
Bore Diameter (mm)	40
Internal Clearance	C0-Medium
Outer Diameter (mm)	52
internal clearance:	Normal Clearance
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.68
Manufacturer Item Number	6808VV
manufacturer upc number:	029176030253
Internal Special Features	No
(Grease) Lubrication Speed	12 000 r/min
Basic static load rating (C0)	5,55 kN
Basic dynamic load rating (C)	6,35 kN
Maximum Capacity /	No

Filling Slot	
--------------	--