



Bearing No. 6808ZZ

r	0.3
d	40 mm
D	52 mm
B	7 mm
C	7 mm
D_	52
C0	5.55
fo	17
ra	0.3
Z_	21
B_	7
DE_	49.969
SRI	2.05
DA_	3.969
DI_	42.031
SRE	2.05
D_a	50
SRIX	0.015
Noun	Bearing
SREX	0.015
SRIN	-0.015
SBRG	18
yobi	6808ZZ
KBRG	6141
Bore	1.575 Inch 40 Millimeter
bomp	0
SDM_	46
SREN	-0.015
mass	0.031

UNSPSC	31171504
Weight	0,031 Kg
r min.	0,3 mm
LangID	1
da min	42
C_conv	6350
ALPHA_	0
da max	42 mm
hidYobi	6808ZZ
GRS rpm	12000
Da max.	50 mm
ra max.	0,3 mm
da min.	42 mm
Category	Single Row Ball Bearing
hidTable	ecat_NSRDGB
Size (mm)	40x52x7
Snap Ring	No
Enclosure	2 Metal Shields
Inventory	0.0
Width (mm)	7
Prod_Type3	DGBB_SR_ZZ
Weight / LBS	1.575
Inch - Metric	Metric
Cage Material	Steel
Product Group	B00308
Bearing number	6808ZZ
Keyword String	Ball
Rolling Element	Ball Bearing
Precision Class	ABEC 1 ISO P0
Long Description	40MM Bore; 52MM Outside Diameter; 7MM Outer Race Diameter; 2 Metal Shields; Ball

	Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Manufacturer URL	http://www.nskamericas.com
Outside Diameter	2.047 Inch 52 Millimeter
Outer Race Width	0.276 Inch 7 Millimeter
Weight / Kilogram	0.035
Manufacturer Name	NSK
Internal Clearance	C0-Medium
Bore Diameter (mm)	40
Outer Diameter (mm)	52
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.68
Internal Special Features	No
(Grease) Lubrication Speed	12 000 r/min
Basic static load rating (C0)	5,55 kN
Basic dynamic load rating (C)	6,35 kN
Maximum Capacity / Filling Slot	No