



Bearing No. 6806NR

| | |
|------|---------|
| f | 0,85 mm |
| r | 0.3 |
| d | 30 mm |
| D | 42 mm |
| B | 7 mm |
| C | 7 mm |
| a | 1,3 mm |
| b | 0,95 mm |
| D2 | 44,8 mm |
| B_ | 7 |
| Cy | 1.8 |
| ra | 0.3 |
| C0 | 3.65 |
| fo | 16.4 |
| D_ | 42 |
| D1 | 40,7 mm |
| rn | 0,3 mm |
| Z_ | 18 |
| Dx | 45.5 |
| ro | 0.25 |
| DE_ | 39.3 |
| DA_ | 3.5 |
| SRI | 1.81 |
| D_a | 40 |
| SRE | 1.81 |
| DI_ | 32.3 |
| SRIN | -0.015 |
| yobi | 6806NR |
| SBRG | 18 |
| bomp | 0 |

| | |
|-------------------------------|---------------|
| SREX | 0.015 |
| KBRG | 6101 |
| SREN | -0.015 |
| SDM_ | 35.8 |
| SRIX | 0.015 |
| mass | 0.024 |
| C_conv | 4700 |
| r min. | 0,3 mm |
| da max | 32 mm |
| ALPHA_ | 0 |
| Weight | 0,024 Kg |
| da min | 32 |
| LangID | 1 |
| GRS rpm | 15000 |
| Da max. | 40 mm |
| hidYobi | 6806NR |
| Oil rpm | 18000 |
| da min. | 32 mm |
| r0 max. | 0,25 mm |
| ra max. | 0,3 mm |
| hidTable | ecat_NSRDGB |
| Size (mm) | 30x42x7 |
| Prod_Type3 | DGBB_SR_NR_OT |
| Width (mm) | 7 |
| Bearing number | 6806NR |
| Bore Diameter (mm) | 30 |
| Outer Diameter (mm) | 42 |
| (Oil) Lubrication Speed | 18 000 r/min |
| (Grease) Lubrication Speed | 15 000 r/min |
| Basic dynamic load rating (C) | 4,7 kN |
| Basic static load rating | 3,65 kN |

| | |
|------|--|
| (C0) | |
|------|--|