



### Bearing No. 6805ZZ

D	37 mm
d	25 mm
B	7 mm
C	7 mm
rn	0,3 mm
Bore	0.984 Inch   25 Millimeter
Noun	Bearing
Weight	0,022 Kg
r min.	0,3 mm
UNSPSC	31171504
da max	28 mm
da min.	27 mm
Da max.	35 mm
ra max.	0,3 mm
series:	68
Category	Single Row Ball Bearing
Enclosure	2 Metal Shields
Size (mm)	25x37x7
Inventory	0.0
Snap Ring	No
Width (mm)	7
bore type:	Round
maximum rpm:	18000 RPM
Weight / LBS	0.044
Cage Material	Steel
Inch - Metric	Metric
Product Group	B00308
closure type:	Double Shielded
bore diameter:	25 mm

Keyword String	Ball
overall width:	7 mm
cage material:	Steel
fillet radius:	0.3 mm
Bearing number	6805ZZ
Rolling Element	Ball Bearing
finish/coating:	Uncoated
Precision Class	ABEC 1   ISO P0
Long Description	25MM Bore; 37MM Outside Diameter; 7MM Outer Race Diameter; 2 Metal Shields; Ball Bearing; ABEC 1   ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Manufacturer URL	<a href="http://www.ntnamerica.com">http://www.ntnamerica.com</a>
Outer Race Width	0.276 Inch   7 Millimeter
Outside Diameter	1.457 Inch   37 Millimeter
outside diameter:	37 mm
outer ring width:	7 mm
inner ring width:	7 mm
Manufacturer Name	NTN
bearing material:	High Carbon Chrome Steel
Weight / Kilogram	0.02
precision rating:	ISO Class 0
Internal Clearance	C0-Medium
Bore Diameter (mm)	25
Outer Diameter (mm)	37
internal clearance:	CN
snap ring included:	Without Snap Ring
Minimum Buy Quantity	N/A

maximum rpm (grease):	18000 rpm
static load capacity:	2950 N
row type & fill slot:	Single Row Non-Fill Slot
dynamic load capacity:	4300 N
Harmonized Tariff Code	8482.10.50.68
Manufacturer Item Number	6805JRZZ/2AS
Internal Special Features	No
(Grease) Lubrication Speed	18 000 r/min
manufacturer product page:	<a href="#">Click here</a>
operating temperature range:	-40 to 120 °C
Basic dynamic load rating (C)	4,3 kN
Basic static load rating (C0)	2,95 kN
Maximum Capacity / Filling Slot	No