



Bearing No. 6805DD

r	0.3
d	25 mm
D	37 mm
B	7 mm
C	7 mm
fo	16.1
D_	37
B_	7
ra	0.3
Z_	16
C0	3.15
DI_	27.3
SRE	1.81
D_a	35
DE_	34.3
SRI	1.81
DA_	3.5
SREN	-0.015
Noun	Bearing
SRIN	-0.015
bomp	0
SRIX	0.015
yobi	6805DD
mass	0.021
SDM_	30.8
KBRG	6191
SREX	0.015
SBRG	18
Bore	0.984 Inch 25 Millimeter

da max	27 mm
Weight	0,021 Kg
da min	27
r min.	0,3 mm
UNSPSC	31171504
ALPHA_	0
LangID	1
C_conv	4500
Da max.	35 mm
ra max.	0,3 mm
da min.	27 mm
hidYobi	6805DD
GRS rpm	10000
Category	Single Row Ball Bearing
hidTable	ecat_NSRDGB
Enclosure	2 Seals
Size (mm)	25x37x7
Snap Ring	No
Inventory	0.0
Prod_Type3	DGBB_SR_DD
Width (mm)	7
bore type:	Round
Weight / LBS	0.02
Product Group	B00308
closure type:	Double Sealed
Inch - Metric	Metric
Cage Material	Steel
Bearing number	6805DD
overall width:	7 mm
Keyword String	Ball
bore diameter:	25 mm
Precision Class	ABEC 1 ISO P0

Rolling Element	Ball Bearing
Outer Race Width	0.276 Inch 7 Millimeter
Long Description	25MM Bore; 37MM Outside Diameter; 7MM Outer Race Diameter; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Manufacturer URL	http://www.nskamericas.com
Outside Diameter	1.457 Inch 37 Millimeter
Weight / Kilogram	0.01
outside diameter:	37 mm
Manufacturer Name	NSK
Internal Clearance	C0-Medium
Bore Diameter (mm)	25
internal clearance:	Normal Clearance
Outer Diameter (mm)	37
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.68
manufacturer upc number:	029176425707
Manufacturer Item Number	6805DD
Internal Special Features	No
(Grease) Lubrication Speed	10 000 r/min
Basic dynamic load rating (C)	4,5 kN
Basic static load rating (C0)	3,15 kN
Maximum Capacity / Filling Slot	No

