



Bearing No. 6805LLU

C	7 mm
d	25 mm
D	37 mm
B	7 mm
Bore	0.984 Inch 25 Millimeter
Noun	Bearing
Weight	0,022 Kg
da max	28 mm
UNSPSC	31171504
r min.	0,3 mm
da min.	27 mm
ra max.	0,3 mm
series:	68
Da max.	35 mm
Category	Single Row Ball Bearing
Enclosure	2 Seals
Size (mm)	25x37x7
Inventory	0.0
Snap Ring	No
Width (mm)	7
bore type:	Round
maximum rpm:	10000 RPM
Weight / LBS	0.045
Cage Material	Steel
Inch - Metric	Metric
closure type:	Double Sealed
Product Group	B00308
bore diameter:	25 mm
Keyword String	Ball

overall width:	7 mm
cage material:	Steel
fillet radius:	0.3 mm
Bearing number	6805LLU
Enclosure Type	Contact Seal
Reference speed	10 000 r/min
finish/coating:	Uncoated
Rolling Element	Ball Bearing
Precision Class	ABEC 1 ISO P0
Outside Diameter	1.457 Inch 37 Millimeter
Manufacturer URL	http://www.ntnamerica.com
Long Description	25MM Bore; 37MM Outside Diameter; 7MM Outer Race Diameter; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Outer Race Width	0.276 Inch 7 Millimeter
outside diameter:	37 mm
precision rating:	ISO Class 0
bearing material:	High Carbon Chrome Steel
Weight / Kilogram	0.02
inner ring width:	7 mm
outer ring width:	7 mm
Manufacturer Name	NTN
Bore Diameter (mm)	25
Internal Clearance	C0-Medium
internal clearance:	CN
snap ring included:	Without Snap Ring
Outer Diameter (mm)	37

Minimum Buy Quantity	N/A
row type & fill slot:	Single Row Non-Fill Slot
maximum rpm (grease):	10000 rpm
static load capacity:	2950 N
dynamic load capacity:	4300 N
Harmonized Tariff Code	8482.10.50.68
Manufacturer Item Number	6805LLU/2A
Internal Special Features	No
manufacturer product page:	Click here
operating temperature range:	-40 to 120 °C
Basic static load rating (C0)	2,95 kN
Basic dynamic load rating (C)	4,3 kN
Maximum Capacity / Filling Slot	No