



Bearing No. 6805N

a	1,3 mm
r	0.3
d	25 mm
D	37 mm
B	7 mm
C	7 mm
b	0,95 mm
fo	16.1
B_	7
ra	0.3
C0	3.15
D1	35,7 mm
D_	37
Z_	16
rn	0,3 mm
ro	0.25
DE_	34.3
SRI	1.81
D_a	35
DA_	3.5
SRE	1.81
DI_	27.3
yobi	6805N
mass	0.021
SBRG	18
bomp	0
KBRG	6101
SREX	0.015
SREN	-0.015
SRIN	-0.015

SDM_	30.8
SRIX	0.015
ALPHA_	0
r min.	0,3 mm
C_conv	4500
da max	27 mm
da min	27
Weight	0,021 Kg
LangID	1
ra max.	0,3 mm
Da max.	35 mm
Oil rpm	22000
da min.	27 mm
r0 max.	0,25 mm
hidYobi	6805N
GRS rpm	18000
hidTable	ecat_NSRDGB
Size (mm)	25x37x7
Prod_Type3	DGBB_SR_N_OT
Width (mm)	7
Bearing number	6805N
Bore Diameter (mm)	25
Outer Diameter (mm)	37
(Oil) Lubrication Speed	22 000 r/min
(Grease) Lubrication Speed	18 000 r/min
Basic dynamic load rating (C)	4,5 kN
Basic static load rating (C0)	3,15 kN