



Bearing No. 6804VV

D	32 mm
d	20 mm
B	7 mm
C	7 mm
r	0.3
Z_	13
B_	7
D_	32
ra	0.3
C0	2.47
fo	15.5
DI_	22.1
SRI	1.81
D_a	30
DE_	29.1
DA_	3.5
SRE	1.81
SRIN	-0.015
SBRG	18
yobi	6804VV
SDM_	25.6
SREX	0.015
KBRG	6151
bomp	0
mass	0.017
Bore	0.787 Inch 20 Millimeter
SRIX	0.015
SREN	-0.015
Noun	Bearing

ALPHA_	0
da min	22
LangID	1
r min.	0,3 mm
UNSPSC	31171504
da max	22 mm
C_conv	4000
Weight	0,017 Kg
ra max.	0,3 mm
hidYobi	6804VV
GRS rpm	22000
da min.	22 mm
Da max.	30 mm
Category	Single Row Ball Bearing
hidTable	ecat_NSRDGB
Snap Ring	No
Size (mm)	20x32x7
Enclosure	2 Seals
Inventory	0.0
Width (mm)	7
Prod_Type3	DGBB_SR_VV
Weight / LBS	0.017
Cage Material	Steel
Product Group	B00308
Inch - Metric	Metric
Bearing number	6804VV
Keyword String	Ball
Enclosure Type	Non-Contact Seal
Precision Class	ABEC 1 ISO P0
Rolling Element	Ball Bearing
Outer Race Width	0.276 Inch 7 Millimeter
Outside Diameter	1.26 Inch 32 Millimeter

Long Description	20MM Bore; 32MM Outside Diameter; 7MM Outer Race Diameter; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Manufacturer URL	http://www.nskamericas.com
Weight / Kilogram	0.01
Manufacturer Name	NSK
Internal Clearance	C0-Medium
Bore Diameter (mm)	20
Outer Diameter (mm)	32
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.68
Manufacturer Item Number	6804VV
Internal Special Features	No
(Grease) Lubrication Speed	22 000 r/min
Basic static load rating (C0)	2,47 kN
Basic dynamic load rating (C)	4 kN
Maximum Capacity / Filling Slot	No